

AR SERIES Buggy

The 0.45 cubic metre AR16 and the 0.59 cubic metre AR21 have earned their rank as the standard by which all power buggies are judged. Their massive 50mm thick solid steel tank-tough frames provide unparalleled strength and durability along with a lower center of gravity and ideal weight distribution. These buggies give excellent traction in real-world job site conditions. Drive components are protected by a removable steel shroud. This shroud is louvered to keep concrete out while providing proper ventilation and cooling to the engine compartment. The standard high-strength, high-density polyethylene bucket is the industry's thickest and most durable. And standard features like heavy-duty hydraulic wheel motors, steel raceways for hydraulic hose protection and optional foam-filled tires ensure the AR16 and AR21 Power Buggies will operate for the duration under tough conditions.

FEATURES:

- Huge 0.45 or 0.59 Cubic Metre Capacity, Heavy-Duty Poly Dump Bucket
- Hydraulic Dump Action
- Foam-Filled Tires Are Optional
- Solid 50mm Thick Steel Frame
- Isolated Steering Column
- Easy-Squeeze Speed Control Lever
- Enclosed Engine Shroud
- Side-To-Side and Rear-To-Front Forklift Pockets
- Foot-Operated Dumping Mechanism



Model	AR16	AR21
Engine	Honda™ GX390 (389 cc) Recoil or Electric Start	Honda™ GX630 (688 cc) Electric Start
Payload (kg)	1,134	1,451
Dimension - L x H (m)	2.46 x 1.27	2.46 x 1.27
Length - With Platform Up (m)	2.25	2.25
Dimensions - Width (m)	1.19	1.19
Wheelbase / Track Length (m)	1.02	1.02
Bucket Capacity (m³)	0.45	0.59
Weight (kg)	Poly Bucket: 590 Steel Bucket: 658	Poly Bucket: 637 Steel Bucket: 710
Lift Cylinder (mm)	ø 51.0	ø 63.5
Dump/Return Speed Empty (sec)	5.0	8.0
Top Speed (km/h)	11.2	9.5
Fuel Capacity (litre)	6.0	8.9

AT SERIES Track Buggy

The ALL-NEW 0.45 cubic metre AT16 Power Buggy with Track Drive provides excellent traction on grades, inclines, and soft soils. Providing more horsepower, more load carrying capacity and greater bucket volume than competitors; the new track buggy's rugged steel frame increases load weight and distributes the load across the entire frame, providing for smooth, even transport.

FEATURES:

- Huge 0.45 cubic metre Bucket Capacity for more productivity.
- Hydraulic Dump Action with 152mm of ground clearance when fully dumped.
- Heavy-Duty Poly Dump Bucket for long life.
- Highest Track Buggy Horsepower Available at 27hp.
- Largest Track Buggy Payload Available at 1,134kg
- Rubber Tracks For Extra Load Capacity and Traction.



Model	AR16
Engine	Kohler Vertical Shaft (27 hp) Electric Start
Payload (kg)	1,135
Dimension - L xH (m)	2.60 x 1.66
Length - With Platform Up (m)	2.24
Dimensions - Width (m)	0.9
Wheelbase / Track Length (m)	3.02
Bucket Capacity (m ³)	0.45
Weight (kg)	Poly Bucket: 669
Lift Cylinder (mm)	ø 64
Dump/Return Speed Empty (sec)	7.0
Top Speed (km/h)	Work: 6km/h Travel: 10km/h
Fuel Capacity (litre)	22.7