



MATERIAL SPREADER MS40C



Ideal for all types of after-pour applications, such as hardeners, colourings, and light reflective coatings!

- Available in 2.5' (0.7 m), 5' (1.5 m), and 10' (3 m) sections.
- Material flow is adjustable from 2 ounces (0.05kg) to 3 pounds (1.4kg) per square foot.
- Bridge section weights only 7lbs (3.2kg) per foot. Hydraulically agitated hopper weights 385lbs (175kg).
- Flow rate control is independent from hopper travel speed.
- Hopper height is adjustable from 2" (5.0 cm) to 18" (45.7 cm) over slab.
- Bolted construction makes on-site length changes and adjustments quick and easy using everyday tools.
- Metered flow valve assures precise application of expensive toppings.
- The MS40 is capable of spanning slabs from 10' (3 m) to 75' (23 m).



Options

- Wheeled end section with 2 or 4 wheels per end.
- Trap rock discharge adaptors.
- Calibration pan 1 lb (0.45 kg) weight, 1ft² (0.3 m²) area.

Specification MS40C		
Engine	Honda GX200	
Power	5.5 HP	
Capacity	4.5 cubic ft. (127 L)	
Maximum Load	600 lbs (272 kg)	
Discharge Height	Adjustable from 2' (5.0 cm) to 18' (121.9 cm)	
Discharge Width	47" (122 cm)	
Weight	Hopper	385 lbs (175 kg)
	2.5' (0.7 m) section	17.5 lbs (8 kg)
	5' (1.5 m) section	32 lbs (14.5 kg)
	10' (3 m) section	61 lbs (28 kg)
	Wheel Assembly	270 lbs (123 kg)
Span	up to 75' (23 m)	

Additional information on accessories and consumables for our Material Spreaders is available through our website, or contacting one of the Bartell Family numbers below.



1-866-501-1683
375 Annagem Blv. Mississauga,
ON, Canada, L5T 3A7
www.bartellmorrison.com



1-888-999-1570
200 Commerce Dr. Freehold,
NJ, U.S.A, 00728
www.bartellmorrison.com



44-(0)1673-860709
Honeyholes Lane, Dunholme
Lincoln. LN2 3SU. U.K.
www.spe-int.com



1-800-267-6682
832 80th St. SW. Everett,
Washington, U.S.A, 98203
www.innovatechproducts.com