

Allen Triple Roller Tube Pavers (TRTP) are specifically designed for paving large projects fast, accurately and efficiently. These pavers are not only the best engineered for their tasks, they're the best value. Allen is so confident in their Paving Equipment that they back them with a One Year, 100% Satisfaction Guarantee! Available in a variety of standard configurations, Allen will also customize their equipment to fit your specific paving projects.

Precision engineered tubes ensure the smoothest pavement possible. Powered by rugged Diesel Engines, with easy to operate control systems, the Triple Roller Tube Paver can strike off concrete fast. And with Allen's precision engineered and level-tested roller tubes, you can be assured of producing the flattest paving job possible.



255CD on the job



*Shown with Vibration System

FEATURES:

- Operational Gang Vibration System for up to 610mm deep concrete consolidation
- Vibrator Head Diameter: 60 mm
- Vibrator Head Length: 600 mm
- Three Super-Flat Roller Tubes
- Vibrator Spacing: 61 cm center to center with radius of effectiveness up to 48 cm
- Water Spray System keeps Tubes clean and smooth
- Pendulum Shaft Driven Vibrators can be adjusted from 0-11,000 VPM from operator console

Model	255CD
Engine	32HP Kubota® Diesel (3.7m-6.0m) 44HP Kubota® (6.7m-10.4)
Widths Available (600mm Increments)	3.6 - 10.4m
Weight at 6.7metre (kg)	2,526
Roller Tube Diameter (mm)	255
Tube Weight Per 300mm (kg)	12
Hydraulic Oil Reservoir (litre)	95.0
Hydraulic Spray System	Standard
Hydraulic Steering Leg	Standard